

MICRO-DEVAL ABRASION TESTER (AG-195) EN 1097-1

- Used to determine the abrasion-resistance of the aggregate particles.
- The machine is made of a rigid steel frame on which one of the following combinations can be mounted:
 - 4 cylinders (Ø 200 mm x 154 mm)
 - 2 cylinders (Ø 400 mm x 154 mm)
 - 2 cylinders (Ø 200 mm x 154 mm) and 1 cylinder (Ø 400 mm x 154 mm)
- Transparent safe guard is fixed on the machine to increase the safely level and insure fault-less environment.
- Equipped with automatic digital counter.
- Supplied with:
 - 2 cylinders (Ø 200 mm x 154 mm)
 - Abrasive Charges - Ø 10 mm (20 kg)



Micro-Deval Testing Abrasion Tester (AG-195)

TECHNICAL SPECIFICATIONS

- Rigid Steel Frame
- Stainless Steel Drums Ø 200 mm x 154 mm (2 ea)
- Safety Guard, Transparent
- Automatic Digital Counter
- Abrasive Charges - Ø 10 mm (20 kg)
- Power Supply: 220 - 240 V / 50 or 60 Hz (110 V / 60 Hz is also available)

Code	Dimensions (± 1 cm)
AG-195	142 x 47 x 46 (h)