

## WATER BATH (G-040)

EN 12697:34 • ASTM D1559 • ASTM D5581 • AASHTO T245

- Used to cure specimens at constant temperature.
- Exterior is made of powder coated steel and the interior tank and the cover are corrosion-resistant stainless steel.
- Supplied with perforated stainless steel shelf which stands at the bottom of the tank to ensure uniform temperature.
- Equipped with digital thermoregulator with range of ambient to 82°C (180°F) and pilot light heat indicator.
- The tank is insulated from the outer cabinet with thick mineral wool to reduce thermal loss and to help maintain constant temperature.
- Available in 2 different capacities and with/without water circulation options.



Water Bath (G-040/30)

### SUPPLIED WITH

- Digital Thermostat & Indicator
- Stainless Steel Cover
- Base Shelf
- Pilot Lamp

### TECHNICAL SPECIFICATIONS

- Digital Thermostat & Indicator
- Interior Stainless Steel
- Water circulation is optional (to be specified at the time of order)
- Power Supply: 220 - 240 V / 50 or 60 Hz (110 V / 60 Hz is also available)



Water Bath (G-040/60)

Code	External Dimensions (± 1 cm)	Internal Dimensions (± 1 cm)	Volume	Approximate Weight (kg)
G-040/30	12" x 20" x 8" 305 x 508 x 203 mm	13-¾" x 21-½" x 15" 350 x 550 x 380 mm	7.93 gallons 30 liters	15
G-040/60	20" x 24-½" x 8" 508 x 622 x 203 mm	21-½" x 31-½" x 15" 550 x 800 x 380 mm	15.85 gallons 60 liters	30