

POCKET PENETROMETER (T-304)

- Used to determine the classification of cohesive soil based on its consistency, shear strength and the approximate unconfined compressive strength.
- The range is (0 – 5) kgf/cm²
- Equipped with a peak value indicator and supplied with a carrying case.



Pocket Penetrometer (T-304)

SUPPLIED WITH

- Case

TECHNICAL SPECIFICATIONS

- Range: 0-5 kgf / cm²
- Peak Value Indicator

Code	Dimensions (± 1 cm)	Approximate Weight (kg)
T-304	Dia: 2 / h: 17	0.2

DIAL PENETROMETER (T-308)

- Used to determine the angle of friction, the cohesion index and the approximate unconfined compressive strength.
- Can be used on the foundation soil from clayey soil to sandy soil.
- The diameter of the dial is 60 mm, and equipped with a peak value holder.
- The Zero Setting for the equipment can be done by pushing the reset button.
- Consists of 5 different plungers to meet the required need, with diameters as follows:
 - 6.35 - 10 - 15 - 20 - 25 mm diameter



Dial Penetrometer (T-308)

TECHNICAL SPECIFICATIONS

- Dial Diameter : 60 mm
- Peak Value Holder
- Zero Setting by Push Button
- 5 Different Plungers:
 - 6.35-10-15-20-25 mm diameter

Code	Dimensions (± 1 cm)	Approximate Weight (kg)
T-308	7.0 x 14.5 x 3.5 (h)	0.2