

SAND EQUIVALENT SHAKER (R040M)

Category: Aggregate



Product Code: R040M

Category: AGGREGATE

Sub-Category: GEOMETRICAL PROPERTIES

-
- Used to provide a constant, uniform, and precise shaking for the sand sample in the cylindrical measure used in Sand Equivalent Test Set. Highly recommended to be used in

laboratories , to minimize variations caused by operators.

- Sand Equivalent Shaker is designed to hold the graduated cylinder securely in a horizontal position while subjecting it to a reciprocating motion parallel to its length and having a throw of $200\text{ mm} \pm 10\text{ mm}$ and operating at 175 cpm.
- Moving parts of the Sand Equivalent Shaker are provided with a hinged safety guard for protection of the operator.

TECHNICAL SPECIFICATIONS

- Stroke : $200\text{ mm} \pm 10\text{ mm}$
- Rate : 175 cpm
- 220 - 240 V / 50 - 60 Hz

EQUIPPED WITH

- Digital Stroke Indicator with automatic shut-off function
- Hinged safety guard for protection of the operator

ORDERING INFORMATION

Code	Item
R 040 M00X T	SAND EQUIVALENT SHAKER - Motorized
R 040 M00X K	SAND EQUIVALENT SHAKER - Motorized [60 Hz]
R 040 H00X H	SAND EQUIVALENT SHAKER - Manual

Keywords: