

MARSHALL COMPACTOR (Automatic, Triple) (A017)

Category: Asphalt



Product Code: A017

Category: ASPHALT

Sub-Category: MARSHALL STABILITY

-
- Used to determine the resistance of asphalt sample to plastic flow. The test is performed in a fully automatic mechanism and programmed to stop automatically at the required

number of blows.

- Supplied with the standard height and rammer weight according to ASTM/EN standards.
- Equipped with a blow counter, wooden pedestal and quick action clamping.

STANDARDS

ASTM D6926 • EN 12697-10 • AASHTO t245

TECHNICAL SPECIFICATIONS

- Consists of 3-mould structure that can compact 3 specimens at the same time
- Blow Rate: 55 ± 5 blows per minute
- Rammer Diameter: $100.33 \text{ mm} \pm 0.25 \text{ mm}$
- Rammer Weight: $4536 \text{ g} \pm 9 \text{ g}$
- Drop Height: $457.205 \text{ mm} \pm 0.635 \text{ mm}$
- 220 - 240 V / 50 - 60 Hz

ORDERING INFORMATION

Item Name	Item Code
TRIPLE MARSHALL COMPACTOR, AUTOMATIC, STATIONARY BASE - ASTM [60 Hz]	A017M04AK
TRIPLE MARSHALL COMPACTOR, AUTOMATIC, STATIONARY BASE - ASTM [50 Hz]	A017M04AT

Keywords: