

ACKCIO BATTERY PACK (N645)

Category: Monitoring



Product Code: N645

Category: MONITORING

Sub-Category: DATALOGGER

-
- The Ackcio BEAM-BP is an external battery pack designed to extend the operational lifetime of Ackcio BEAM wireless nodes in remote or long-term monitoring installations.
 - Developed for harsh environmental conditions, the BEAM-BP enables continuous and autonomous power supply where external energy sources are unavailable or impractical.

- The pack accommodates up to eight Li-SOCl₂ D-cell batteries (3.6 V nominal, 19 Ah recommended capacity) arranged in pairs, ensuring high energy density and stable output voltage under varying load conditions.
 - Featuring IP67-rated protection and a wide operating temperature range from –40 °C to +80 °C, the BEAM-BP is engineered for outdoor and underground applications.
 - The system includes a dedicated Battery Adaptor that regulates voltage output (6 V - 24 V input range) for reliable connection to compatible Ackcio BEAM nodes.
 - Output circuits are fuse-protected to prevent overload, ensuring long-term safety and performance in demanding environments.
 - The BEAM-BP currently supports Ackcio BEAM-DG Digital Nodes, with support for additional BEAM models under development.
 - It can be easily mounted alongside Ackcio nodes using standard clamps or brackets for compact, maintenance-friendly installation.
-

TECHNICAL SPECIFICATIONS

- Model: BEAM-BP (with Battery Adaptor)
- Battery Configuration: Up to 8 × D-cell Li-SOCl₂ 3.6 V batteries (pairs: 2, 4, 6 or 8)
- Recommended Capacity: 19 Ah per cell
- Power Output (Battery Pack): 7.2 V max, 1 A max (fuse protected @ 2 A)
- Power Output (Adaptor): 3.8 V max, 400 mA max
- Input (Adaptor): 6 V - 24 V DC
- Input Wiring: Screw clamp terminals (0.2 - 1.5 mm² / 24 - 16 AWG)
- Protection: Fuse protection, reverse polarity protection, IP67 enclosure
- Operating Temperature: –40 °C to +80 °C
- Material: Die-cast aluminium housing
- Power Source: Non-rechargeable battery pack (no external supply required)
- Compatibility: Ackcio BEAM-DG Digital Nodes (current), future BEAM node support under development

ORDERING INFORMATION

To be added soon ...

Keywords: Ackcio BEAM-BP, external battery pack, Ackcio Mesh, BEAM-DG power supply, Li-SOCl₂ battery pack, wireless node power, long-term monitoring battery, geotechnical monitoring power supply, IP67 battery enclosure, low-power IoT battery system, field instrumentation accessory